

## **Developing project evaluation models for smart sustainable practices initiatives in construction projects: A case of Nigeria and Hong Kong**

### **Abstract**

**Purpose:** The purpose of this paper is to identify the key facilitating factors for smart sustainable practices (SSP) and develop a project evaluation model (PEM) for SSP implementation in Nigeria and Hong Kong. SSP is coined from the integration of digital technologies such as Building Information Modelling (BIM) to facilitate sustainability.

**Design/methodology/approach:** The study employed a quantitative research design approach using empirical questionnaire surveys to solicit the opinions of 69 and 97 construction practitioners in Nigeria and Hong Kong. Purposive and snowball sampling techniques were used to identify the potential survey respondents. The fuzzy synthetic evaluation technique was used to develop the PEMs.

**Findings:** The findings revealed that adequate knowledge and technical expertise of the SSP processes are critical to enhancing its implementation in Hong Kong and Nigeria; as well as the provision of training programs for cross-field specialists in smart and sustainable initiatives. Meanwhile, the study's findings revealed that for an SSP-enabled construction project, its project performance is mostly influenced by the client's satisfaction level and the early involvement of the project teams. However, in Nigeria, effective partnership, which considers the involvement of green-conscious project stakeholders, a supportive organizational structure is a key influencing factor.

**Practical implications:** Construction stakeholders in developing and developed countries can utilize the PEMs to determine and track SSP initiatives implementation in building projects in a reliable and practical way. The study also provides project teams with a checklist of key factors to consider when digital tools are employed to facilitate sustainability in construction works.

**Research limitations:** The study's results are limited to the Nigeria and Hong Kong construction industries.

**Originality/value** – No tool has been developed for evaluating SSP initiatives at the project level in the construction industry. Using case studies of Hong Kong and Nigeria, PEM indices were developed to measure and track SSP implementation in construction projects. More so, the proposed PEMs provide a common basis to compare the implementation levels of SSP in construction projects.

**Keywords:** BIM; construction projects; fuzzy synthetic evaluation; smart sustainable practices; Nigeria; Hong Kong

## 1. Introduction

Globally, there has been increased attention and growing initiatives by international and non-governmental organizations, environmental groups, countries, and other stakeholders to stem the tide of climate change, greenhouse gas emissions, global warming, waste generation, among others. The construction industry itself is a major contributor to these environmental issues. As buildings are constructed yearly, more energy is consumed, and there are increased carbon emissions (Tam *et al.*, 2019). Also, enormous resources such as materials and energy are expended in producing a building product (Ljungberg, 2007), most of which goes for its production and transportation than what is used for such product itself.

For instance, buildings in the United States contribute 48% of its total greenhouse gas (GHG) emissions, while construction wastes constitute a larger percentage of Hong Kong's environmental waste (Wong and Fan, 2013). Generally, the global contributions of the construction industry to these sustainability challenges stand at 40% for solid waste generation (UNEP, 2011), 32% for energy consumption (IPCC, 2007), and 35% for material usage (Ürge-Vorsatz *et al.*, 2007).

Due to the growing concerns about these environmental challenges, green buildings and sustainable practices implementation (Olawumi and Chan, 2020b) has emerged as a key project objective in the construction industry. Also, technological approaches are being advanced as an enabling tool towards implementing sustainable principles in the building environment (Blagojevic and Tufegdžic, 2016). For instance, BIM can be used to embed relevant sustainable design information to improve the building performance, efficiency, and cost. A study by Wong and Fan (2013) shows BIM is useful in selecting the best design solutions that offer better energy and resource consumption. In Europe, the European Commission has proposed using smart systems to drive sustainable development (Russo *et al.*, 2016), one of which is investment in the 'Lighthouse' initiative, which seeks to facilitate smart-sustainable development in European cities (European Union ODP, 2018).

In some countries, there has been the development of green building rating systems (GBRS) to facilitate the assessment and rating of building projects and guide developers and project teams on aspects to focus on in delivering a green building project. For instance, we have BEAM Plus in Hong Kong (HKGBC, 2019), the BSAM Scheme in Nigeria (Olawumi *et al.*, 2020), BREEAM, and LEED in the UK and USA (BRE, 2016; USGBC, 2018), respectively. Also, there has been the application of BIM software for energy analysis, daylighting, and assessing building sustainability performance (Motawa and Carter, 2013). Other applications of technologies for smart-sustainable practices implementation include the use of radio frequency identification (RFID) and BIM (Fang *et al.*, 2016) for indoor localization; BIM for

energy simulation (Oloke, 2021), and most recently, blockchain technology is being adopted to facilitate sustainability in the construction supply chain (Shojaei *et al.*, 2019). Also, Dall'O' *et al.* (2020) explored the integration of Green-BIM and city information modelling to design and manage buildings and infrastructures to achieve sustainability and smart schemes. Based on the review of several digital technologies used for sustainability implementation in construction projects, BIM is mostly adopted for its application. One of the reasons for the increased use of BIM for SSP implementation; apart from its adoption rate (which is higher than most other digital tools used in the construction industry) – is that BIM produces better useful data along with relevant information in the forms of visualizations and simulations (Motawa and Carter, 2013).

Hence, smart-sustainable practices are considered 'digital technocentric' approaches to facilitating sustainable principles, green and sustainable buildings or cities, and improving the overall construction process (Martin *et al.*, 2019; Olawumi and Chan, 2019a). Along with this perspective, Banihashemi *et al.* (2017) utilized the innovation diffusion theory to identify key drivers that affects the integration of sustainability for project management practices in developing countries; while Antón and Díaz (2014) and Lu *et al.* (2017) explored that application of BIM for green buildings. Also, Olawumi and Chan (2019b) developed a benchmarking model to assess BIM implementation in developing countries, while Tai *et al.* (2020) evaluated key criteria that influence BIM adoption in China.

Moreover, Zhao *et al.* (2016) developed a risk assessment model for green building projects in Singapore, which share similar characteristics with Hong Kong; and Aghimien *et al.* (2020) examined the challenges of smart city development in developing countries in Nigeria. However, no studies have considered how to measure the level of application of SSP in construction projects and the influence of key facilitating factors on SSP implementation. Having a PEM metric system in place to measure SSP implementation will guide construction practitioners on identifying the requirements and factors that affect its application and how to move toward higher adoption of SSP initiatives in construction projects.

Given the above, this paper aims to address these research gaps by identifying and assessing the key facilitating factors and developing a project evaluation model (PEM) for smart sustainable practices implementation in Nigeria and Hong Kong. The project evaluation models for Nigeria and Hong Kong are developed in this study using the fuzzy synthetic evaluation (FSE) technique. The study's findings will present construction practitioners in both countries with a checklist of key facilitating factors for SSP implementation, which can be useful as a consultative tool to drive green building development. More so, the proposed PEM in this study will provide project teams, clients,

and other critical stakeholders with a metric system in measuring the level of application of SSP in construction projects. More so, the proposed PEMs provide a common basis to compare the implementation levels of SSP initiatives construction projects. It is expected that the practical deliverables of this study will improve the adoption and implementation of smart-sustainable practices in Nigeria and Hong Kong.

Moreover, in the extant literature and practice, in assessing the global construction industry, two main dimensions are usually employed – either based on (i) classification by regions or (ii) level of development (developing or developed countries). The level of development is more of a homogenous classification that has gained traction in usage among authors and international organizations such as the World Bank and International Monetary Fund. Some key indices used to classify countries into developed and developing countries include countries which share similar: (i) macroeconomic environment (Austin, 2002; Toor and Ofori, 2008; Saini and Singhania, 2018); (ii) socio-political conditions (Austin, 2002; Saini and Singhania, 2018); (iii) human capital and technological gap (Toor and Ofori, 2008; Goswami and Saikia, 2012; Alam and Shah, 2013). Moreover, World Bank (2020) used the Gross National Income per capita of US\$ 12,536 or less to classify countries into developing countries and vice versa. Hence, these indices were used to classify Nigeria and Hong Kong in this study and form the basis for recommending the possible application of the proposed smart sustainable practice PEMs to other developing and developed countries that share these key indices with Nigeria and Hong Kong.

**Scope.** Hong Kong was used as a case study in this research (apart from being a financial hub in the Asia region); it is also one of the very few countries globally which have advanced the use of BIM (Chan *et al.*, 2019a) and sustainability in the construction industry. For developing countries, especially in Africa, Nigeria has the largest economy (Terwase *et al.*, 2014) and the biggest construction market, making it suitable as a focal point for investigation. Also, there is a growing awareness of BIM and sustainability practices in the country. Moreover, BIM being the most popular digital technology adopted globally in the construction industry (Jung and Lee, 2015), was considered the prime digital tool in the context of “digital technology” in developing the PEMs for smart-sustainable practices in this study.

## **2. Background**

### **2.1 Overview of smart sustainable practices**

The concept of sustainability is widely accepted across various spectrums of stakeholders. However, there are divergent opinions regarding how to apply sustainable practices in the built environment, especially the construction industry. One of the reasons advanced for the

ununiformed approach to sustainability is its complexity (Clark, 2002) and because it involves a mix of conceptual and quantitative metrics (Ekins *et al.*, 2003; Mahmoud *et al.*, 2019). As a result, environmental sustainability received much concern from developed nations while socio-economic sustainability criteria are given preference in developing countries (Ahmad and Thaheem, 2017). Moreover, this is also evident in the various sustainability standards and guidelines developed in these countries – for example, the GBRS available in countries such as the United States, United Kingdom, Hong Kong, Australia, and the like are focused on building-related environmental issues (Olawumi *et al.*, 2020).

Sustainability concepts in the built environment are usually associated with terms such as green buildings (Ahmad and Thaheem, 2017), sustainable design and construction (Jalaei and Jrade, 2015), zero-carbon buildings (Gupta *et al.*, 2014), and the like. These sustainable initiatives in buildings have helped mitigate some environmental and socio-economic problems associated with the conventional building process (Maleki and Zain, 2011). Although sustainable development is multidimensional and integrated in scope (Slimane, 2012), its application in built assets and infrastructure has mostly been unidirectional. More so, the construction industry faces problems in delivering green and sustainable projects due to a mirage of several factors (Zhao *et al.*, 2015; Shi *et al.*, 2016).

As a result, digital technologies and tools are being advanced to help solve the challenge involved in delivering green building projects and infrastructure (Martin *et al.*, 2018) and facilitate the integration of sustainable designs. This development has brought about the concept of smart-sustainable practices, which is fast becoming a key driver for facilitating green building and other sustainable initiatives in the built environment (De Jong *et al.*, 2015). The digital technocentric approach to the delivery of sustainable initiatives in construction projects can also help facilitate an automated construction process, digitalized supply chains, and smart buildings and cities.

A few digital technologies have been adopted in extant literature to integrate SSP in practices. For instance, Jeong *et al.* (2016) explored the implementation of BIM and simulation tools to incorporate sustainability principles in building designs and construction projects as well as incorporating the future needs of end-users. Giglio (2010) stressed the capabilities of BIM to be deployed across the building stages for energy analysis, data capture, and visualizations, and in cloud-based environments. Hence, this offers the clients and project team a cost-advantage because the data from a previous building analysis at an earlier stage could be useful at a later stage without a need for reinvestment. Meanwhile, Rivera *et al.* (2015) attempted to investigate the intersections of using technological solutions for smart-sustainable initiatives. The study stressed the need for adopters to

understand the lock-in effects and vulnerabilities associated with using digital tools for SSP and recommended that the adopted technologies be seen as a neutral facilitator that carries no implicit values (Rivera *et al.*, 2015).

The capability of BIM to aid in smart-sustainable initiatives lies in its nD functionality, especially the 7D BIM, which provides the best avenue to incorporate relevant sustainable designs and practices in building projects. Moreover, some studies envisioned that big data has future prospects of supporting the smart-sustainable initiatives in the built environment (Bibri, 2019; Shukla and Mattar, 2019). Despite the benefits and prospects of adopting SSP initiatives in the built environment, adopters must factor in the related challenges associated with its implementation (Belli *et al.*, 2020). In contributing to the existing knowledge base of smart sustainable practices, the current study presents SSP project evaluation models that assist measure and keep track of its implementation.

## **2.2 Smart sustainable practices in Nigeria and Hong Kong**

The city of Hong Kong has significantly made milestones in the areas of smart-sustainable practices compared to Nigeria. For instance, the BEAM Plus green building rating system was launched in 1996 in Hong Kong, and four green buildings were assessed the same year using the BEAM Plus (BEAM Society, 2021). Currently, the BEAM Plus has been used to assess more than 500 buildings in the city. Meanwhile, the first GBRS system in Nigeria was developed in the year 2019. Although it has been used to evaluate four building projects in the country (Olawumi and Chan, 2020a), it is yet to gain traction in usage among industry folks. Also, digital technologies such as BIM are being advanced in the city by industry and professional organizations such as the Construction Industry Council (CIC) and the Hong Kong Institute of Building Information Modelling (Chan *et al.*, 2019b).

Although BIM is still at its early stages of adoption in Hong Kong, it has found significant usage in mega projects like Hong Kong airport, the mass transit rail, and among private property developers (Wong *et al.*, 2009; Chan *et al.*, 2019b), and more recently in the first hybrid modular construction project in Hong Kong – “InnoCell.” These projects' success has enhanced the acceptance of SSP initiatives in the ‘eyes of the clients.’ Although the level of awareness of BIM in the Nigerian construction industry is quite above average, the usage rate does not commensurate (Hamma-adama *et al.*, 2018). As noted by Olawumi and Chan (2019a), the level of BIM implementation in a project has a significant resultant effect on the adoption of smart sustainable practices in such projects. Moreover, unlike in Nigeria, there is a government mandate to adopt BIM in public construction projects in Hong Kong. Its use is also currently high among the private sector players (Chan *et al.*, 2019b). Also, As promoted by CIC Hong Kong, there are some BIM standards for different construction works. Given

the above, the adoption level of smart sustainable practices in both contexts varies – while it is low in Nigeria and other African countries, it is rated between medium-high level in Hong Kong (Jung and Lee, 2015; Olawumi and Chan, 2018).

Govada *et al.* (2020) reviewed the various efforts directed towards implementing smart sustainable practices in Hong Kong, including environmental policies in areas like green building, zero-carbon buildings, and smart technologies. Adopting these SSP initiatives is imperative in a densely compact city of over 7 million residents in less than 1200km<sup>2</sup> land areas. However, the city is still lacking in areas like energy savings and recycling (Govada *et al.*, 2020). Furthermore, a comparative study of the SSP initiatives implemented in 14 global megacities was undertaken by Shmelev and Shmeleva (2019). In the comparative analysis, Hong Kong was ranked fifth behind major cities like Singapore and Sydney on environmental initiatives. Meanwhile, for economic initiatives, Hong Kong was ranked third behind Tokyo and London; however, as regards social and smart initiatives, Hong Kong was ranked outside the top-five megacities (Shmelev and Shmeleva, 2019). Moreover, a study by Chan and Marafa (2018) presented divergent results from that of Shmelev and Shmeleva (2019), in that the sampled Hong Kong residents opined that the city is performing “smarter” than “greener.” These studies show that although Hong Kong is pulling its weight in the global SSP initiatives, there are still many improvements to be made. Hence, developing a PEM to measure and track smart sustainable initiatives in Hong Kong is imperative.

Meanwhile, an analysis of the SSP initiatives in selected countries by Estevez *et al.* (2016) shows that Nigeria is still a long way from adopting these initiatives with just one smart-sustainable initiative implemented in the country, compared to four in neighboring Ghana as well as in Kenya. The US, Korea, and China topped the list with 11, 6, and 5 initiatives, respectively. Hence, Adamu *et al.* (2017) stressed the need for Nigeria’s cities to implement relevant SSP initiatives as the country faces an upsurge in urban dwellers (Antwi-Afari *et al.*, 2021) with its attendant environmental and social challenges. More so, similar to Hong Kong, Nigeria is also faced with issues such as environmental wastes and energy (Adamu *et al.*, 2017; Govada *et al.*, 2020) as well as transportation challenges. Sustainable transportation is a key assessment criterion in major GBRS like LEED, BREEAM, BEAM Plus, and the BSAM scheme (HKGBC, 2016; BRE, 2018; USGBC, 2018; Olawumi *et al.*, 2020). Meanwhile, Adamu *et al.* (2017) proposed ways in which Nigeria could achieve the smart-sustainable initiative, while Soyinka *et al.* (2016) investigated the applicability of using smart concepts to facilitate the implementation of sustainable practices in Lagos, a key commercial hub in Nigeria. Most African countries also face similar challenges as Nigeria, as captured by Lampreia *et al.* (2019) in the study’s review of challenges faced in Africa in implementing SSP initiatives.

### **2.3 Fuzzy synthetic evaluation**

The fuzzy synthetic evaluation (FSE) technique was used in this study to develop the proposed project evaluation models for SSP implementation in Hong Kong. The study in developing the PEMs relies on data based on the survey respondents' perceptions, which are often subjective and ambiguous (Shan *et al.*, 2015). Hence, the application of fuzzy set theory using FSE to objectifies the survey respondents' judgement. The fuzzy set theory provides the capability to reduce issues relativity to ambiguity, uncertainty, and subjectivity in the decision-makers' judgement (Pedrycz *et al.*, 2010).

It also has an advantage over the artificial neural network technique as regards the precision of its resultant data (Liao *et al.*, 2019), as fuzzy methods use mathematical operators to quantify the available data (Zhao *et al.*, 2016; Aghimien *et al.*, 2020). It also utilizes linguistics variables to analyze subjective viewpoints which might occur in the decision-making process. More so, per (Xu *et al.*, 2010), FSE is very suitable for a decision-making process involving multiple stakeholders. Thus, the FSE approach is considered appropriate in developing the PEMs for SSP implementation in Nigeria and Hong Kong. Moreover, the FSE technique has found applications in the development of models and indexes in areas like green buildings (Zhao *et al.*, 2016), BIM (Liao *et al.*, 2019), project performance (Hu *et al.*, 2016; Osei-Kyei and Chan, 2018), among others. In general, the FSE technique's strength lies in evaluating data involving several variables across different levels. The subsequent section discusses the analytical approaches and equations adopted in employing the FSE technique in developing the PEMs for smart sustainable practices for Nigeria and Hong Kong.

## **3. Research methodology**

A quantitative research design approach was employed in this study using empirical questionnaire surveys to aggregate construction practitioners' responses in Nigeria and Hong Kong and apply relevant statistical tools in developing the PEMs for smart-sustainable practices implementation. The overall research design for this study is illustrated in Figure 1. The questionnaire items are based on a shortlist of key factors adapted (see Table 1) from a previous study (Olawumi and Chan, 2020c), where the drivers of smart sustainable practices in the construction industry were examined from a global perspective. The reuse of an itemized list of factors is common in the literature, such as a study by Darko *et al.* (2018), who reused and adapted a list of measurement constructs from their previous studies for further analysis. Other instances are in the extant literature is a two-part research study published in Tsai *et al.* (2014) and Mom *et al.* (2014), in which the latter study is a continuation of the former research on BIM adoption in Taiwan.



### **Insert Figure 1**

Moreover, for this study, taking into cognizance the guidelines provided by Cheng and Phillips (2014) in conducting such research work, the current study adopted a research question-driven approach, which involves recoding the original variables. The key differences in this study and those reported in Olawumi and Chan (2020c) are that the current study examined the key factors based on the context of two countries – Nigeria and Hong Kong, rather than a global perspective. Secondly, this study analyzed a set of survey data to develop a metric system to measure SSP implementation in Nigeria and Hong Kong. In contrast, the previous study focused on ranking the critical factors based on an inter-group comparison of key professionals worldwide. Thus, the current study differs in scope and objectives.

### **Insert Table 1**

#### **3.1 Demographics of the survey respondents**

**Selection criteria and sampling.** An empirical questionnaire survey was conducted with experts in Hong Kong and Nigeria who have requisite practical knowledge and experience in sustainability practices or BIM adoption in construction projects. Nigeria and Hong Kong are chosen as the research area due to the authors' established contacts within these countries' construction industries. The respondents known to the authors were contacted directly via a purposive sampling approach, and other responses were obtained using the snowball sampling technique. For the snowballing sampling, practitioners' email addresses in government agencies and construction firms were gleaned from their organization websites. These respondents were sent personalized emails inviting them to participate in the survey if they have the requisite experience required to participate in the survey. The authors' established industry contacts were also requested to help in the further circulation of the survey forms within their professional circuits. Some of the emails sent to organizations were forwarded to the managers to help circulate them among relevant professionals in their company. Prior to distributing the questionnaire survey form, it was pretested to validate the questionnaire items and its relevance to the research objective.

Meanwhile, relevant information was solicited from the survey respondents, which was used to validate their relevant expertise in the subject matter, as illustrated in Table 2. The survey was conducted over six months. The respondents were also requested to rate their agreement on the significance of the key factors based on a five-point Likert scale (*1 = strongly disagree, 3 = neutral, and 5 = strongly agree*). About 50 percent of the survey forms were distributed by hand or via postal mail in Hong Kong, while the survey forms were distributed via email and other online platforms (such as network groups, Google form) for

the Nigeria context. The respondents from Nigeria were mainly from key commercial cities like Lagos, Ogun, Abuja, Ibadan, and the like. Overall, 69 and 97 survey respondents in Nigeria and Hong Kong returned valid and completed survey forms, which are used for further analysis in this paper.

The study's sample size can be considered adequate as it is above the average range of 20 to 30 survey responses seen in published literature (see Chan & Chan, 2012; Osei-Kyei & Chan, 2018). As shown in Table 2, the survey respondents have relevant expertise and knowledge of implementing BIM and sustainability practices which lends credence and reliability to the data received. Based on the analysis of the organization's setup of the survey respondents, they are mainly from six types of organizations. The bulk of Hong Kong respondents are from government agencies (39%) and contracting firms (25%). Meanwhile, those in Nigeria are mostly from academic institutions (49%) and project consultancy firms (19%). As reported by Dall'O' et al. (2020), organizations that adopt Green-BIM would have the ability and skillset to further integrate sustainable practices in building designs than those who do not. Thus, these statistics might have a say in the higher level of smart sustainable practices implementation in Hong Kong than what is obtainable in Nigeria, as government agencies and contractors are better positioned to implement it in construction projects than academics.

The survey respondents in Nigeria and Hong Kong share a similar opinion that the planning and design stages of a building represent the best opportunity to implement smart sustainable practices in construction projects. Majority of the two sets of respondents have a good level of awareness on how to implement BIM and sustainability practices in the built environment. Examining the average years of experience of the survey respondents from both countries, respondents in Hong Kong have more practitioners with at least 11 years of working experience in the construction industry than those in the Nigeria context.

## **Insert Table 2**

### **3.2 Data analysis tools**

The data collated via the questionnaire surveys were analyzed using SPSSv23 and Microsoft Excel software. The SPSS software was used to determine the mean score (MS) of each driver, perform factor analysis (FA), and analyze the respondents' demographics. Microsoft Excel software was employed to model the fuzzy synthetic evaluation (FSE) analysis of the data and calculate the range normalization values for the driver. The mean score method, a relatively popular statistical tool, was used to rank the factors based on the level of importance (Olatunji *et al.*, 2017).

Factor analysis is a statistical technique capable of reducing a large number of variables to a manageable set by assessing the interrelationships between them (Hair *et al.*, 2010). It is also useful to explain difficult concepts (Xu *et al.*, 2010) and was used to regroup the set of drivers into small groups via the principal component analysis (PCA). As recommended by Xu *et al.* (2010), a Pearson correlation analysis was used in analyzing the perception of the respondents of the key factors before subjecting the data to further analysis via factor analysis. Pearson correlation helps to detect whether any two factors share a linear relationship, that is, whether one of the factors can be explained by the other. However, no statistical relationship ( $p > 0.05$ ) was discovered in this study's data for the Hong Kong dataset. The factor clusters were extracted using the varimax rotation method. Preliminary tests such as the Kaiser-Meyer-Olkin (KMO) tests, correlation matrix, and Bartlett's test of sphericity (BTS) were conducted to determine the factor model's adequacy for factor analysis.

Fuzzy synthetic evaluation is an analytical tool that applies the fuzzy set theory to quantify multi-attribute and multi-evaluation (Xu *et al.*, 2010; Ameyaw and Chan, 2015b). It has found application in risk analysis and allocation (Ameyaw and Chan, 2015a), construction management (Hu *et al.*, 2016; Osei-Kyei and Chan, 2018), among others within the built environment. Like other fuzzy methods, the FSE objectifies the decision-makers' subjective judgements on a subject matter. Hence, it was selected as the appropriate statistical technique in this study. The FSE as a decision-making process, according to Lam *et al.* (2007), consists of linguistics variables, membership functions, fuzzy evaluation matrix, weighting vectors, and the computation of the natural language.

The FSE technique is the main statistical tool used in this study to develop the project evaluation models, based on the FSE modelling approach adopted in the extant literature (Hu *et al.*, 2016; Osei-Kyei and Chan, 2017):

Firstly, the key drivers (criteria) were denoted as  $\pi = \{d_1, d_2, d_3, \dots, d_n\}$ ; where  $n$  represents the number of the criteria. The 5-point Likert scale measurement used in the survey form to evaluate the drivers represents the set of grade categories and are labelled as  $C = \{C_1, C_2, C_3, \dots, C_n\}$ . Where  $C_1$  = strongly disagree,  $C_3$  = neutral, and  $C_5$  = strongly agree. Hence, to calculate each criterion's weighting (driver), we use equation (Eq. 1) and relevant values based are on the data from the survey responses.

$$W_i = \frac{MS_i}{\sum_{i=1}^5 MS_i} \text{ where } 0 \leq W_i \leq 1, \quad \text{and} \quad \sum W_i = 1 \quad \text{--- (1)}$$

Where  $W_i$  = weighting;  $MS_i$  = mean score of a selected criterion (driver), and  $\sum MS_i$  = summation of the mean ratings of the selected drivers.

A fuzzy evaluation matrix for each driver is expressed as  $R_i = (r_{ij})_{m \times n}$ ; where  $r_{ij}$  is the degree to which the grade categories,  $C_j$  satisfies the driver,  $d_j$ . The second-level membership function ( $R_i$ ) of each driver is based on the percentage rating for each  $C_j$  from the collated data. The first-level membership functions of the FSE evaluation model ( $F$ ) is obtained by evaluating the weighting vectors ( $W_i$ ) of the criteria cluster and its fuzzy evaluation matrix ( $R_i$ ) as expressed in Eq. 2:

$$F = W_i \circ R_i \quad \text{----- (2)}$$

Where  $\circ$  is the fuzzy component operator;

The resultant fuzzy evaluation results are normalized to 1, and the PEM index ( $PEM_i$ ) can be calculated using Eq. 3:

$$PEM_i = \sum_{l=1}^5 F \times C \quad \text{----- (3)}$$

These FSE approaches were employed systematically to analyze the survey data and develop the PEMs useful in measuring SSP implementation in Hong Kong and Nigeria's construction industry.

#### 4. Results of statistical analyses

This section presents the results of the various statistical analysis employed in this study. It involves selecting the key drivers (D); establishing the drivers' groupings (DG); generating the weightings and membership functions for each driver and DG and developing the PEMs for smart sustainable practices implementation in construction projects Hong Kong and Nigeria. The data obtained from survey respondents in Nigeria and Hong Kong were analyzed separately and discussed in this section.

##### 4.1 Selecting the key drivers – normalization & correlation analysis

Table 3 shows the ranking by mean score and standard deviation of the drivers for smart sustainable practices implementation in Hong Kong and Nigeria. The mean score values range from MS=3.53 ("*D25– Availability and affordability of cloud-based technology*") to MS=4.12 ("*D1– Technical competence of staff*") for Hong Kong; and MS=3.90 ("*D6– Adequate construction cost allocated to BIM*") to MS=4.54 ("*D1– Technical competence of staff*") for construction projects in Nigeria.

Meanwhile, to select the key drivers, the range normalization method ( $N_m$ ) was employed, and only drivers with normalized values of 0.5 and above are considered for further factor

analysis and FSE analysis. The drivers selected via this mechanism are considered the most significant and critical factor (Xu *et al.*, 2010; Osei-Kyei and Chan, 2017)

$$N_m = \frac{MS_i - MS_a}{MS_b - MS_a}$$

Where  $MS_i$  = mean score for the selected driver;  $MS_a$  = minimum MS for the set of drivers; and  $MS_b$  = maximum MS for the set of drivers.

As shown in Table 3, 18 factors and 15 factors in Nigeria and Hong Kong are rated as critical drivers, respectively, as they have normalized values of 0.5 and above.

Further analysis of these key factors using Pearson correlation analysis shows that for Nigeria's context – factor (D25), “*availability and affordability of cloud-based technology*” was highly correlated with D26 “*interoperability and data compatibility*” at a 5% significance level ( $\rho=0.725$ ). Also, factor (D12), “*development of appropriate legal framework for BIM use and deployment in projects,*” was highly correlated with D16 “*appropriate legislation and governmental enforcement & credit for innovative performance*” ( $\rho=0.736$ ). Hence, only key drivers (D16 & D26) were selected and used for further analysis to avoid the multiplier effect between the variables. Therefore, 16 key drivers are deemed critical within the Nigerian context, and 15 key drivers for the Hong Kong context.

### Insert Table 3

#### **4.2 Establishing the drivers' groupings**

The FA technique using the PCA approach was used to classify the key drivers. The driver groupings (DG) for the Nigeria context were extracted based on the factors' eigenvalues. However, for the Hong Kong context, eigenvalues extraction of factors was not used because it extracted only two clusters – one of which contains factors that are heterogeneous in their characteristics. Hence, FA was used to extract a fixed number of groups without considering the groups' eigenvalues.

The Cronbach alpha analysis (Field, 2009; Olatunji *et al.*, 2017) for the dataset revealed  $\alpha$ -value of 0.977 and 0.949 for Hong Kong and Nigeria, respectively, which is higher than the recommended value of 0.70. It also indicates the questionnaire measures the right construct. Further preliminary test using KMO statistics which measures sampling adequacy, and BTS test shows a KMO value of 0.856 and 0.942 for Nigeria and Hong Kong, respectively, indicating the generated cluster is distinct and reliable. For the BTS analyses, it revealed a high statistic value (chi-square= 1301.230) and small significance value ( $p=0.000$ ;  $df= 105$ ) for the Hong Kong context. For the Nigeria context, the BTS value is the chi-square value of

800.946 and p-value of 0.000 (df=120). This indicates that the two contexts' correlation matrix is not an identity matrix (Chan and Choi, 2015).

As shown in Tables 4 and 5, the drivers' factor loadings are above the recommended value of 0.5. The higher the factor loading of each driver, the higher the driver's significance with its underlying DG (Chan and Hung, 2015). Meanwhile, an identifiable label was attached to each DG which are clusters of the individual factors (Sato, 2005), although these labels are subjective. The four-factor groupings extracted for the Nigeria context using PCA represents 70% of the total variance (Table 4), while for the Hong Kong context, it is 81% (Table 5). These values are above the minimum threshold of 60% (Hair *et al.*, 2010; Chan, 2019).

The four separate factor groupings extracted for the Hong Kong context include knowledge (DDG1), technical specifications (DDG2), project performance and collaboration (DDG3), and finance/cost (DDG4). Each cluster contains at least three underlying factors. For instance, DDG1 consists of D3, D2, D23, and D1; whereas, DDG2 has D10, D28, D15, and D29 has its underlying factors. DDG3 comprises D24, D21, D22, and D27; while DDG4 consists of D6, D7, and D5.

**Insert Table 4**

**Insert Table 5**

### **4.3 Generating the weightings and membership functions for each key driver and drivers' groupings**

For the FSE modelling, two levels are defined. The first level is the drivers' groupings (DGs/DDGs) level, while the second level is the key drivers (Ds) level – which are the underlying factors within each DG.

#### **4.3.1 Determining the weightings of Ds (second level) and DGs/DDGs (first level)**

The weightings of the Ds and the DGs/DDGs are calculated using Eq. 1, which are based on the mean scores of the factors analyzed from the survey responses (Table 6). For instance, for the Nigeria context, DG4 “*Project performance*” comprises three Ds with a total mean score of 13.06, the weighting of criteria “*D22 – Client satisfaction level on BIM projects*” can be obtained as follows:

$$W_{DG4} = \frac{4.25}{4.25 + 4.46 + 4.35} = \frac{4.25}{13.06} = 0.325$$

Therefore, the weightings for all the drivers and driver groupings for the Hong Kong and Nigeria contexts were calculated using Eq. 1.

**Insert Table 6**

### 4.3.2 Determining the membership functions of Ds and DGs/DDGs

Meanwhile, the membership functions for Ds and DGs/DDGs for level 2 and level 1 were derived for the Hong Kong and Nigeria contexts. Membership function values range between 0 and 1 and represent the degree of an element's membership in a fuzzy set (Ameyaw and Chan, 2015a). The membership function of the underlying criteria (Ds) for level 2 is calculated first before evaluating the membership functions of the DGs/DDGs (level 1). The membership functions are derived based on the ratings of the set of grade categories (that is,  $C_1$  = strongly disagree,  $C_3$  = neutral, and  $C_5$  = strongly agree). For example, in the Nigeria context, 1% of the expert *strongly disagree* with driver “D26 – Interoperability and data compatibility” being a key driver for smart sustainable practices implementation. Meanwhile, 2, 10, 42, and 45 percent of the expert also ticked “disagree,” “neutral,” “agree,” and “strongly agree” to the significance of the D26 as a key driver, respectively. Hence, the membership function (MF) of D26 is computed as follows:

$$MF_{D26} = \frac{0.01}{c1} + \frac{0.02}{c2} + \frac{0.10}{c3} + \frac{0.42}{c4} + \frac{0.45}{c5}$$

This MF for D26 is expressed as (0.01, 0.02, 0.10, 0.42, and 0.45). Likewise, the MF for the 15Ds and 16Ds for the Hong Kong and Nigeria contexts, respectively, can be derived using the same approach (Table 7). Having derived the MF at level 2, the MF at level 1 can be calculated using Eq. 2. Hence, using the driver groupings “DDG4 - Finance/Cost” of the Hong Kong context as an example, its MF can be evaluated as follows:

$$F_{DDG4} = \begin{bmatrix} 0.334 \\ 0.334 \\ 0.333 \end{bmatrix} \times \begin{bmatrix} 0.02 & 0.06 & 0.17 & 0.53 & 0.22 \\ 0.02 & 0.01 & 0.25 & 0.53 & 0.19 \\ 0.02 & 0.02 & 0.26 & 0.49 & 0.21 \end{bmatrix} = (0.02 \quad 0.03 \quad 0.23 \quad 0.52 \quad 0.21)$$

Similarly, the remaining 3DDGs of the Hong Kong context and the 4DGs of the Nigeria context were derived, as shown in Table 6 (column 4).

### Insert Table 7

### 4.3.3 Defuzzify the membership functions of DGs/DDGs

The next step in the FSE modelling is the defuzzification of the membership functions at level 1, which will help decision-makers adopt smart sustainable practices. The defuzzification of the MFs of the DGs/DDGs results in the  $PEM_i$  for each of the driver groupings. Eq. 3 was used to defuzzify the MFs. For example, the  $PEM_i$  for “DDG2 – Technical specifications” of the Hong Kong context is computed as follows:

$$P11_{(DDG2)} = (0.02, 0.01, 0.19, 0.57, 0.20) \times (1, 2, 3, 4, 5) = 3.91$$

The same equation was used to defuzzify the MFs of the DGs/DDGs for the Nigeria and Hong Kong contexts, as shown in Table 8.

**Insert Table 8**

**4.4 Developing the overall PEMs for smart sustainable practices implementation in Nigeria and Hong Kong**

The final step in the FSE modelling is the development of the overall  $PEM_i$  models, whereby the  $PEM_i$  of the DDGs/DGs are used in formulating the linear equation model. Linear and additive model was used for the overall  $PEM_i$  modelling because the DDGs/DGs for the Nigeria and Hong Kong contexts do not correlate; that is, there are not linear (Osei-Kyei and Chan, 2017). More so, per Hu et al. (2016) and Yeung et al. (2009), using a linear equation model will make it easier to use and understand by industry practitioners and other users.

Meanwhile, before developing the composite linear model, the  $PEM_i$ , for the DDGs/DGs are normalized to ensure the sum of the resultant coefficients equal to one or unity (Table 8). Normalizing the  $PEM_i$  is logical and valid (Osei-Kyei and Chan, 2017), as it helps to illustrate better the relative activity between the criteria in the linear equation. Essentially, it allows the differing scale of measurements to be used when assessing the key drivers for smart sustainable practices implementation in construction projects.

The PEM for smart sustainable practices implementation in Hong Kong’s construction industry can be expressed as:

$$PEM_i = (0.255 \times Knowledge) + (0.249 \times Technical\ specifications) \\ + (0.250 \times Project\ performance\ \&\ collaboration) \\ + (0.246 \times Finance/cost) \quad \text{---(4)}$$

Also, the PEM for smart sustainable practices implementation in Nigeria’s construction industry is:

$$PEM_i = (0.253 \times Knowledge\ \&\ Enforcement) + (0.250 \times Effective\ partnership) \\ + (0.246 \times Technical\ specifications) \\ + (0.251 \times Project\ performance) \quad \text{---(5)}$$

**5. Discussion of results and practical implications**

The  $PEM_i$  models as presented in Eqs. 4 and 5 revealed: “Knowledge” (0.255) and “Knowledge & Enforcement” (0.253) with the highest coefficient for the Hong Kong and Nigeria contexts, respectively. Ranked second for Hong Kong and Nigeria are the “Project performance & collaboration” (0.250) and “Project performance” (0.251) respectively;



meanwhile, “Effective partnership” (0.250) is ranked third in PEM for Nigeria and is partly similar to ‘*collaboration*’ (2<sup>nd</sup> ranked in the Hong Kong context). “Technical specifications” (0.249) is the third-ranked in the Hong Kong context but ranked fourth with a coefficient of 0.246 in Nigeria’s PEM. The sum of all coefficients in each of the two PEMs equals one (Table 8).

The developed PEMs equations and models would substantially enable industry practitioners and other stakeholders to practically evaluate the implementation level of smart sustainable practices in their construction projects. More so, the  $PEM_i$  models provide a common basis for its users to compare the SSP implementation levels in construction projects. Furthermore, the driver groupings that constitute the PEMs for Hong Kong and Nigeria will be discussed in the following sub-sections.

## **5.1 Driver groupings**

### **5.1.1 Knowledge and Enforcement**

The driver grouping (DG1) accounts for 46.243% of the total variance for the Nigeria context and also has the highest  $PEM_i$  value of 4.40, with a coefficient of 0.253. Similarly, for the Hong Kong context, the driver grouping (DDG1 – “Knowledge”) has the highest  $PEM_i$  value of 4.00 with a coefficient ( $\rho$ ) of 0.255. The two related driver groupings – *DG1* and *DDG1* – have two underlying factors in common, which are “*technical competence of staff*” (D1) and “*more training programs for cross-field specialists in BIM and sustainability*” (D3). These key factors are ranked top-three in the Hong Kong and Nigeria contexts (Table 3). The mean ranking and  $PEM_i$  analyses reveal that to enhance the adoption of SSP initiatives, the training, awareness, and expertise of relevant practitioners must be thoroughly emphasized by construction organizations, professional bodies, and even the government.

Morlhon *et al.* (2014) and Chan *et al.* (2019a) underscored the importance of knowledge and awareness of construction stakeholders, academics, and practitioners in improving the adoption of SSP initiatives in the built environment. The studies further stressed the significance of coercive pressures or mandates by government and private clients in ensuring the implementation of SSP in construction projects. To put it in context, when practitioners are knowledgeable and skilled in how and when to apply smart and sustainable initiatives, there are more inclined to adopt them for future construction projects. More so, when project teams, contractors, and other critical components of the construction supply chain are aware that to secure a contract, it would be expected of them to show evidence of being sustainability conscious. They would facilitate their staff’s training and provide relevant financial and organizational support in improving their SSP status. Other key factors within the driver groupings include “*establishment of a model of good practice for BIM and*

*sustainability execution*" (D10) and "*appropriate legislation and governmental enforcement*" (D16) under DG1 of the Nigeria context as well as "*supportive organizational culture and effective leadership*" (D23) and "*greater awareness and experience level within the firm*" (D2) under DDG1 of the Hong Kong context.

The driver, "*D1– technical competence of staff*", has the highest weightings and mean ranking within the groupings (DG1–  $W=0.259$ ,  $MS=4.54$ ; DDG1–  $W=0.258$ ,  $MS=4.12$ ). In the Nigerian construction industry, as well as other developing countries, the little or lack of 'expected' level of technical competency in deploying BIM infrastructure and integrating sustainability issues in projects have impeded the progress being made to adopt the SSP initiatives (Hamma-adama *et al.*, 2018; Lampreia *et al.*, 2019). As evident in other regions such as North America and Europe, where significant efforts and resources have been deployed in improving the overall technical and professional expertise of construction stakeholders (Jung and Lee, 2015; Olawumi and Chan, 2018); which has resulted in the development of more greener cities and buildings.

It is envisioned that if construction firms and government agencies in Nigeria and other developing countries devote resources in equipping construction workers with the relevant skillset to deploy SSP initiatives, it will produce similar results as seen in the advanced worlds. Although the adoption of smart sustainable practices implementation is above average in Hong Kong compared to Nigeria (Chan *et al.*, 2019a), this factor is still a key driver in Hong Kong. As reported by Govada *et al.* (2020), Hong Kong lags in implementing digital technologies to implement energy savings and recycling. Hence, efforts should be directed towards these areas in Hong Kong. More so, as pointed out by Ozorhon and Karahan (2016) and Rogers *et al.* (2015), the more the number of professionals with requisite experience in SSP, the easier its implementation.

Another key factor in the groupings is "*D3 – more training programs for cross-field specialists in BIM and sustainability*" is somewhat related to D1 given that such training programs would further enhance the technical competence of such specialists (Jalaei and Jade, 2014). It is the second-ranked driver in the Nigerian context and third-ranked in the Hong Kong context. The provision of required training and workshops (Succar *et al.*, 2013) in the various aspects of sustainability and innovative tools like BIM will equip such staff and practitioners with skills and knowledge to facilitate smart sustainable practices. Specifically, in Hong Kong, a supportive structure and leadership (D23) are considered key drivers to its implementation. D23 is somewhat linked to D10, which is a key driver in Nigeria. Hence, it is important for construction firms, stakeholders to develop in-house strategies and guidelines for its implementation (Won and Lee, 2010). Also, the *development of useful models of good practice* (D10) for smart sustainable practices (Antón and Díaz, 2014), such as the

development of the BSAM scheme green building rating system for sub-Saharan Africa (Olawumi *et al.*, 2020). Notably, there is a need for regulatory and professional enforcement (D16) of its implementation in the Nigerian construction industry.

### 5.1.2 Project performance and Effective partnership

The DDG3 “*project performance & collaboration*” is the second-ranked driver grouping ( $PEM_i = 3.92$ ,  $\rho = 0.250$ ) in the Hong Kong context while DG4 “*project performance*” ( $PEM_i = 4.36$ ,  $\rho = 0.251$ ); and DG2 “*effective partnership*” ( $PEM_i = 4.34$ ,  $\rho = 0.250$ ) which are the second and third-ranked driver groupings within the Nigeria contexts are discussed in this section under a combined driver grouping “*project performance and effective partnership (PPEP)*.” Majority of the underlying drivers in this driver cluster (PPEP) are ranked within the top ten-ranked drivers in both the Hong Kong and Nigeria context. D21 is ranked third among the key drivers in the Nigeria context but ranked sixth in the Hong Kong context (Table 3).

The driver “*D21 – early involvement of project teams*” (Kassem *et al.*, 2012) is a significant driver in both contexts. It is the highest-ranked in both the DG2 and DG4 groupings ( $W = 0.342$ ,  $MS = 4.46$ ) of the Nigeria context and ranked second in the DDG3 ( $W = 0.252$ ,  $MS = 3.94$ ) of the Hong Kong context. The contractual arrangements for most construction projects have been identified as a key barrier to implementing innovative and disruptive concepts (Saka *et al.*, 2019) such as BIM and sustainability. The most common, which is traditional procurement, only allows the contractor to bid for the job. As such, the contractor and some other relevant stakeholders have no influence on the project design. Hence, there is a need for a unique procurement route that will involve the participation of relevant stakeholders, including external stakeholders such as environmental groups, to facilitate the implementation of SSP initiatives.

More so, there is a need to create a stimulating and conducive environment that will support and encourage collaboration and coordination (D9) among the project stakeholders (Hanna *et al.*, 2014). It will be counterproductive to engage the relevant project stakeholders early in a project without providing common data and a collaborative working environment to facilitate their decision-making on SSP implementation in the construction project. More so, the level of client’s satisfaction (D22) as regards the SSP initiatives implemented in the construction project (Ahn *et al.*, 2014; Rogers *et al.*, 2015) provides a good indicator to measure its success and could facilitate the implementation of SSP by the clients in future projects.

### 5.1.3 Technical specifications

The driver grouping (DDG2) is the third-ranked driver grouping in the Hong Kong context ( $PEM_i = 3.91$ ,  $\rho = 0.249$ ) while DG3 is ranked fourth in the Nigeria context ( $PEM_i = 4.28$ ,  $\rho = 0.246$ ). There are two related drivers in both contexts, which are D15, “*Establishment of BIM standards, codes, rules, and regulations*,” and D29, “*Availability of BIM and sustainability databases*” and factor (D15) is well ranked in both contexts (Table 3). There are three key drivers of the SSP initiatives in the Nigeria context and four in the Hong Kong context. These key drivers can be considered significant, with their mean scores ranging from  $MS = 3.88$  (D10) to  $MS = 4.30$  (D15). Essentially, to advance the implementation of smart sustainability practices in the built environment, there is a need to develop, provide, and streamlined the necessary technical specifications required to ease its adoption.

Key driver (D15) is the most significant driver in both contexts (DG3–  $W = 0.335$ ,  $MS = 4.30$ ; DDG2–  $W = 0.255$ ,  $MS = 3.99$ ). The inadequacy or nonexistence of relevant standards and regulations to guide BIM adoption, according to Redmond *et al.* (2012) and Chan *et al.* (2019b), has derailed the implementation of smart sustainable practices in most countries. Currently, there are no industry BIM standards in Nigeria; although there are some relevant BIM standards in Hong Kong developed by the CIC, it has not received an industry-wide acceptance. As BIM is a critical component of smart sustainable practices implementation (Wong and Zhou, 2015), as advanced in this study, stakeholders should devote resources towards developing BIM standards that suit their local context.

Similarly, there is a need to enhance the information sharing protocol between relevant software and processes (D26). Saxon (2013) emphasized that issues relating to interoperability and data incompatibility hinder information processing and effective collaboration. More so, as the implementation of smart sustainable practices relies heavily on information processing, this driver is considered very significant in enhancing its uptake. Meanwhile, the provision and availability of relevant BIM and sustainability databases (D29) are considered a significant driver (Abolghasemzadeh, 2013) to implement SSP initiatives in Nigeria and Hong Kong. The availability of these databases will ensure uniformity in the file naming, data formats, and BIM object identification, which will ease the coordination of its implementation. It is important to note that prompt and efficient support from software vendors (D28) will also aid SSP implementation.

### 5.1.4 Finance/Cost

Driver grouping (DDG4) is the fourth-ranked in the Hong Kong context ( $PEM_i = 3.86$ ,  $\rho = 0.246$ ) and comprises of three underlying drivers (D6, D7 & D5). D5 has the least mean

score and weightings ( $MS=3.85$ ,  $W=0.333$ ), and factor D7 is ranked the most significant driver in the grouping. As earlier postulated, smart sustainable practices are heavily reliant on information management via the various BIM and associated software. Hence, there is a need for strategic policies by construction firms and relevant stakeholders to allocate funds to purchase relevant BIM software and licenses (D7). Nanajkar and Gao (2014) argued that commitment to investing in technology infrastructures and software by top management would aid the implementation of smart sustainable practices in construction projects.

Furthermore, the support from the government via direct funding, subsidies, incentives (D5) construction firms will aid their adoption of smart sustainable practices (Suermann and Issa, 2009; Abubakar *et al.*, 2014). It is recommended that the bulk of such start-up funds for construction firms should be allocated for small and medium-scale firms. In a similar vein, such funding should be provided for firms with a strategic framework to implement SSP initiatives in their construction projects. Meanwhile, a significant barrier to its implementation is the cost of integrating BIM and associated tools in construction projects. Hence, to ameliorate this limitation, Kivits and Furneaux (2013) and Olawumi and Chan (2020c) pointed out that the client should allocate sufficient funds for BIM implementation in the project. As such, in future projects, when such a construction firm has achieved a satisfactory level of smart sustainable practices, the percentage sum allocation for BIM and other associated software will invariably reduce overtime.

## **5.2 Practical research implications**

The proposed PEMs for smart-sustainable practices (Eqs. 4 & 5) were developed in this study using the FSE technique to objectively quantify the various key factors that influence SSP in Nigeria and Hong Kong's construction industry, respectively. By adopting the PEMs, construction practitioners are provided with a useful tool to measure the level of application of smart-sustainable practices in construction projects. The implementation level of a given construction project can be determined by using the PEM models to calculate the index of each DG/DDG in the equations for Nigeria and Hong Kong, respectively. Its users could adopt two approaches to determine the index of each driver groupings: (i) the practitioners should assess the degree/level of achievement of the underlying key drivers of each driver groupings on a scale of measurement (that is, 5-, 7-, or 9-point scale). Furthermore, the average  $PEM_i$  for each DG/DDG should be determined and substituted in the PEMs (Eqs. 4 & 5). (ii) Another approach is for the practitioners to redo the entire fuzzy synthetic evaluation method presented in this study using a new dataset.

Meanwhile, using the PEMs (Eqs. 4 & 5), practitioners in Hong Kong and Nigeria can reliably and objectively compare the implementation levels of smart sustainable practices in

construction projects. The comparison can also be used for benchmarking purposes. The key drivers and driver groupings provide useful indicators and checklists for practitioners, clients, government agencies, and other stakeholders on the core areas to focus and allocate resources towards enhancing SSP implementation in Hong Kong and Nigeria. The identified key drivers can also be useful as a consultative toolkit to aid the implementation of green and sustainable buildings and cities.

The PEM models developed for Hong Kong would benefit the local construction industry and could be applicable in other regions. Similarly, developing countries in Africa and other regions would find the PEM model developed for Nigeria applicable to their local context to measure the level of implementation of smart-sustainable practices in their construction projects. It will also improve the adoption and implementation of SSP initiatives in these regions.

The authors recommend using smart-sustainable practices PEMs to evaluate construction projects at the pre-construction phases – especially at the design and post-tender stages before the project is contracted out. It is also advised for the PEM re-evaluation of construction projects to be undertaken again midway within the construction process to validate the actual implementation of smart-sustainable practices in the project.

Moreover, the proposed smart-sustainable practices PEMs being a project-based tool would be most beneficial and useful for the clients/employer and project teams to evaluate the construction project. Also, in a design and build contract, where the main contractor is involved early in the project planning and decision-making process, the PEM could be a useful tool for the contractor to plan and assess the construction project's SSP initiatives.

According to Yuan *et al.* (2019), shaping clients' adoption behaviors is critical in improving BIM adoption for sustainability. One of the approaches identified in the study is the provision of tools, technical requirements, and other resources to guide practitioners (Elhendawi *et al.*, 2019; Yuan *et al.*, 2019) – which the current study has achieved with the (i) development of the PEM tool for smart-sustainable practices implementation and (ii) the provision of a checklist of key factors to consider when digital tools are being employed to facilitate sustainability in construction works

## **6. Conclusions**

The construction industry in Nigeria and Hong Kong has been making significant steps towards integrating smart and sustainable practices in the built assets and infrastructure in relation to the fast-paced development in its urban cities. However, both contexts are still not close to achieving it, as evident in previous studies and practice. Although previous studies

attempted to conceptualize the challenges faced by Nigeria and Hong Kong's built environment, none has presented a tool or model to measure the level of application of SSP in construction projects. Hence, the current study attempts to bridge this gap via the development of PEMs for SSP in both contexts.

The PEMs for smart-sustainable practices implementation was developed in this study using the FSE technique, which is a derivative of the fuzzy set theory. The FSE method was useful in handling the subjective opinions of the survey respondents that were used in the development of the PEMs and via the use of mathematical operators help to achieve precise evaluation. More so, as the invited practitioners provided their responses in linguistic forms, using the FSE, the proposed project evaluation models were developed with less subjectivity and ambiguity. Moreover, as discussed in section 5.2, the proposed PEMs can be considered objective, practicable, and applicable within the context of Nigeria and Hong Kong, respectively. The proposed PEMs also provide a common basis for practitioners to measure or compare SSP initiatives' implementation levels in construction projects. The study also presents practitioners with a checklist of key facilitating factors for SSP implementation, which can be useful as a consultative tool to drive green and sustainable building development. The proposed PEMs developed in this study also contribute to existing knowledge and practice by assisting clients and other stakeholders in measuring and tracking the levels and stages of their implementation of SSP initiatives.

The 30 key factors of SSP were used in the questionnaire survey, of which 69 and 97 responses were received from practitioners in Nigeria and Hong Kong, respectively. After subjecting the collected data to various statistical analyses, including the Pearson correlation test and normalization tests - only 16 key factors were used to develop the PEM for the Nigerian context. Meanwhile, 15 critical factors were used for the PEM development for the Hong Kong context. Using factor analysis, the two sets of key factors were categorized into four groups each. The results obtained for the key factors indicated that "technical competence of staff," "more training programs for cross-field specialists in BIM and sustainability," "early involvement of project teams," and "greater awareness and experience level within the firm" are significant adoption drivers of SSP in Nigeria and Hong Kong based on their mean values. More so, based on the index value of the driver groupings derived using the FSE technique – "knowledge and enforcement" and "collaboration and value" in Nigeria; and "knowledge" and "project performance and collaboration" in Hong Kong are critical to their achievement of SSP initiatives.

A limitation of the study is that the research was conducted in Nigeria and Hong Kong and may not be directly applicable to other developing or developed worlds, respectively. However, since these contexts share similar sociopolitical and economic features with other

countries, this study's research outputs might still be relevant beyond the scope of Nigeria and Hong Kong, respectively. As the current study is a case study of Hong Kong and Nigeria, future research can focus on using and supplementing the factors in this study to facilitating comparison in other climes. A practical application of the smart sustainable practices' PEM in some case study projects is proposed to advance its use by practitioners in the construction industry.

## References

- Abdirad, H. (2017) 'Metric-based BIM Implementation Assessment : A Review of Research and Practice', *Journal of Architectural Engineering and Design Management*, 13(1), pp. 52–78. doi: 10.1080/17452007.2016.1183474.
- Abolghasemzadeh, P. (2013) 'A comprehensive method for environmentally sensitive and behavioral microscopic egress analysis in case of fire in buildings', *Safety Science*. Elsevier Ltd, 59, pp. 1–9. doi: 10.1016/j.ssci.2013.04.008.
- Abubakar, M., Ibrahim, Y. M., Kado, D. and Bala, K. (2014) 'Contractors Perception of the Factors Affecting Building Information Modelling (BIM) Adoption in the Nigerian Construction Industry', *Computing in Civil and Building Engineering* ©ASCE, pp. 167–178.
- Adamu, A. A., Wang, D. and Adam, A.-F. (2017) 'Smart cities: the foundation for future citizen service delivery in Nigeria', *American Journal of Engineering Research (AJER)*, 6(3), pp. 161–167.
- Adamus, L. W. (2013) 'BIM: Interoperability for Sustainability Analysis in Construction', in Petr Hájek, Jan Tywoniak, Antonín Lupíšek, Jan Růžička, K. S. (ed.) *Central Europe towards Sustainable Building 2013: Integrated building design BIM*. Prague, Czech Republic: CESB13, Czech Technical University, pp. 1–4. Available at: [http://cesb.cz/cesb13/proceedings/4\\_design/CESB13\\_1120.pdf](http://cesb.cz/cesb13/proceedings/4_design/CESB13_1120.pdf).
- Aghimien, D. O., Aigbavboa, C., Edwards, D. J., Mahamadu, A. M., Olomolaiye, P. *et al.* (2020) 'A fuzzy synthetic evaluation of the challenges of smart city development in developing countries', *Smart and Sustainable Built Environment*. doi: 10.1108/SASBE-06-2020-0092.
- Ahmad, T. and Thaheem, M. J. (2017) 'Developing a residential building-related social sustainability assessment framework and its implications for BIM', *Sustainable Cities and Society*. Elsevier B.V., 28, pp. 1–15. doi: 10.1016/j.scs.2016.08.002.
- Ahn, K. U., Kim, Y. J., Park, C. S., Kim, I. and Lee, K. (2014) 'BIM interface for full vs. semi-



- automated building energy simulation', *Energy and Buildings*. Elsevier B.V., 68(PART B), pp. 671–678. doi: 10.1016/j.enbuild.2013.08.063.
- Aibinu, A. and Venkatesh, S. (2014) 'Status of BIM Adoption and the BIM Experience of Cost Consultants in Australia', *Journal of Professional Issues in Engineering Education Practice*, 140(Autodesk 2011), pp. 1–10. doi: 10.1061/(ASCE)EI.1943-5541.0000193.
- Akinade, O. O., Oyedele, L. O., Ajayi, S. O., Bilal, M., Alaka, H. A. *et al.* (2017) 'Design for Deconstruction (DfD): Critical success factors for diverting end-of-life waste from landfills', *Waste Management*. Elsevier Ltd, 60, pp. 3–13. doi: 10.1016/j.wasman.2016.08.017.
- Aksamija, A. (2012) 'BIM-Based Building Performance Analysis : Evaluation and Simulation of Design Decisions Integration of BIM-Based Performance Analysis with Design', in *ACEEE Summer Study on Energy Efficiency in Buildings*, pp. 1–12.
- Alam, A. and Shah, S. Z. A. (2013) 'Determinants of foreign direct investment in OECD member countries', *Journal of Economic Studies*, 40(4), pp. 515–527. doi: 10.1108/JES-10-2011-0132.
- Alsayyar, B. and Jrade, A. (2015) 'Integrating Building Information Modeling (BIM) With Sustainable Universal Design Strategies To Evaluate the Costs and Benefits of Building Projects', in *5th International/11th Construction Specialty Conference*, pp. 1–10.
- Ameyaw, E. E. and Chan, A. P. C. (2015a) 'Evaluation and ranking of risk factors in public-private partnership water supply projects in developing countries using fuzzy synthetic evaluation approach', *Expert Systems with Applications*. Elsevier Ltd, 42(12), pp. 5102–5116. doi: 10.1016/j.eswa.2015.02.041.
- Ameyaw, E. E. and Chan, A. P. C. (2015b) 'Risk allocation in public-private partnership water supply projects in Ghana', *Construction Management and Economics*. Routledge, 33(3), pp. 187–208. doi: 10.1080/01446193.2015.1031148.
- Antón, L. Á. and Díaz, J. (2014) 'Integration of LCA and BIM for Sustainable Construction', *International Journal of Social, Behavioral, Educational, Economic, Business and Industrial Engineering*, 8(5), pp. 1378–1382.
- Antwi-Afari, P., Owusu-Manu, D.-G., Simons, B., Debrah, C. and Ghansah, F. A. (2021) 'Sustainability Guidelines to Attaining Smart Sustainable Cities in Developing Countries: A Ghanaian Context.', *Sustainable Futures*. Elsevier Ltd, 3(December 2020), p. 100044. doi: 10.1016/j.sfr.2021.100044.
- Austin, J. E. (2002) *Managing in developing countries: strategic analysis and operating*

*techniques*. London, UK: Collier Macmillan Publishers.

Azhar, S. (2011) 'Building Information Modeling (BIM): Trends, Benefits, Risks, and Challenges for the AEC Industry', *Leadership and Management in Engineering*, 11(3), pp. 241–252.

Banihashemi, S., Hosseini, M. R., Golizadeh, H. and Sankaran, S. (2017) 'Critical success factors (CSFs) for integration of sustainability into construction project management practices in developing countries', *International Journal of Project Management*. Elsevier Ltd, APM and IPMA, 35(6), pp. 1103–1119. doi: 10.1016/j.ijproman.2017.01.014.

BEAM Society (2021) *Milestones*, BEAM. Available at: [https://www.beamsociety.org.hk/en\\_about\\_us\\_2.php](https://www.beamsociety.org.hk/en_about_us_2.php) (Accessed: 18 February 2021).

Becerik-gerber, B. and Kensek, K. (2010) 'Building Information Modeling in Architecture, Engineering, and Construction: Emerging Research Directions and Trends', *Journal of Professional Issues in Engineering Education and Practice*. 1801 ALEXANDER BELL DR, RESTON, VA 20191-4400 USA: ASCE-AMER SOC CIVIL ENGINEERS, 136(3), pp. 139–147. doi: 10.1061/(ASCE)EI.1943-5541.0000023.

Belli, L., Cilfone, A., Davoli, L., Ferrari, G., Adorni, P. *et al.* (2020) 'IoT-Enabled Smart Sustainable Cities: Challenges and Approaches', *Smart Cities*, 3(3), pp. 1039–1071. doi: 10.3390/smartcities3030052.

Bibri, S. E. (2019) 'Data-driven smart sustainable urbanism: the intertwined societal factors underlying its materialization, success, expansion, and evolution', *GeoJournal*. Springer Netherlands, 86(1), pp. 43–68. doi: 10.1007/s10708-019-10061-x.

Blagojevic, M. R. and Tufegdžic, A. (2016) 'The new technology era requirements and sustainable approach to industrial heritage renewal', *Energy and Buildings*. PO BOX 564, 1001 LAUSANNE, SWITZERLAND: ELSEVIER SCIENCE SA, 115(SI), pp. 148–153. doi: 10.1016/j.enbuild.2015.07.062.

Bolgani, M. (2013) 'The Implementation of BIM within the public procurement: A model-based approach for the construction industry', *VTT Technology, Finland*, p. 130.

BRE (2016) *BREEAM In-Use International (Technical Manual)*. 2nd edn. Hertfordshire: BRE Global Ltd.

BRE (2018) *BREEAM UK New Construction (Non-domestic Buildings)*. Hertfordshire: BRE Global Ltd.

Chan, C. S. and Marafa, L. M. (2018) 'Knowledge-perception bridge of green-smart

- integration of cities: An empirical study of Hong Kong', *Sustainability (Switzerland)*, 10(1). doi: 10.3390/su10010107.
- Chan, C. T. W. (2014) 'Barriers of Implementing BIM in Construction Industry from the Designers' Perspective: A Hong Kong Experience', *Journal of System and Management Sciences*, 4(2), pp. 24–40.
- Chan, D. W. M. (2019) 'Sustainable building maintenance for safer and healthier cities: effective strategies for implementing the Mandatory Building Inspection Scheme (MBIS) in Hong Kong', *Journal of Building Engineering*, 24 (July), p. Article Number 100737, 13 pages. doi: 10.1016/j.jobe.2019.100737.
- Chan, D. W. M. and Chan, J. H. L. (2012) 'Developing a performance measurement index (PMI) for target cost contracts in construction: a delphi study', *Construction Law Journal*, 28(8), pp. 590–613. Available at: <http://repository.lib.polyu.edu.hk/jspui/handle/10397/5364>.
- Chan, D. W. M. and Choi, T. N. Y. (2015) 'Difficulties in executing the Mandatory Building Inspection Scheme (MBIS) for existing private buildings in Hong Kong', *Habitat International*. Elsevier Ltd, 48, pp. 97–105. doi: 10.1016/j.habitatint.2015.03.015.
- Chan, D. W. M. and Hung, H. T. W. (2015) 'An empirical survey of the perceived benefits of implementing the Mandatory Building Inspection Scheme (MBIS) in Hong Kong', *Facilities*, 33(5/6), pp. 337–366. doi: 10.1108/F-09-2013-0066.
- Chan, D. W. M., Olawumi, T. O. and Ho, A. M. L. (2019a) 'Critical success factors for building information modelling (BIM) implementation in Hong Kong', *Engineering, Construction and Architectural Management*, 26(9), pp. 1838–1854. doi: 10.1108/ecam-05-2018-0204.
- Chan, D. W. M., Olawumi, T. O. and Ho, A. M. L. (2019b) 'Perceived benefits of and barriers to Building Information Modelling (BIM) implementation in construction: The case of Hong Kong', *Journal of Building Engineering*. Elsevier Ltd, 25(September), p. Article Number 100764, 10 pages. doi: 10.1016/j.jobe.2019.100764.
- Cheng, H. G. and Phillips, M. R. (2014) 'Secondary analysis of existing data: opportunities and implementation', *Shanghai Archives of Psychiatry*, 26(6), pp. 371–375. doi: 10.11919/j.issn.1002-0829.214171.
- Clark, T. W. (2002) *The policy process: A practical guide for natural resource professionals*. New Haven, CT: Yale University Press.
- Dall'O, G., Zichi, A. and Torri, M. (2020) 'Green BIM and CIM: Sustainable Planning Using

- Building Information Modelling', in Dall'O', G. (ed.) *Green Planning for Cities and Communities. Research for Development*. Cham: Springer International Publishing, pp. 383–409. doi: 10.1007/978-3-030-41072-8.
- Darko, A., Chan, A. P. C., Yang, Y., Shan, M., He, B. J. *et al.* (2018) 'Influences of barriers, drivers, and promotion strategies on green building technologies adoption in developing countries: The Ghanaian case', *Journal of Cleaner Production*. Elsevier Ltd, 200, pp. 687–703. doi: 10.1016/j.jclepro.2018.07.318.
- Deutsch, R. (2011) *BIM and Integrated Design: Strategies for Architectural Practice*. Hoboken: John Wiley & Sons.
- Ekins, P., Simon, S., Deutsch, L., Folke, C. and Groot, R. De (2003) 'A Framework for the practical application of the concepts of critical natural capital and strong sustainability', *Ecological Economics*, 44(2–3), pp. 165–185. doi: 10.1016/S0921-8009(02)00272-0.
- Elhendawi, A., Omar, H., Elbeltagi, E. and Smith, A. (2019) 'Practical approach for paving the way to motivate BIM non-users to adopt BIM', *International Journal of BIM and Engineering Science*, 2(2), pp. 1–22. Available at: [http://www.academia.edu/download/61862273/Practical\\_approach\\_for\\_paving\\_the\\_way\\_to\\_motivate\\_BIM\\_non-users\\_to\\_adopt\\_BIM20200122-7123-jmzvw2.pdf](http://www.academia.edu/download/61862273/Practical_approach_for_paving_the_way_to_motivate_BIM_non-users_to_adopt_BIM20200122-7123-jmzvw2.pdf).
- Estevez, E., Lopes, N. and Janowski, T. (2016) *Smart Sustainable Cities: Reconnaissance Study*. Canada: United Nations University. doi: 10.1007/s11726-011-0521-5.
- European Union ODP (2018) *CORDIS - EU research projects under Horizon (2014 -2020), H2020 research projects*. Available at: <https://data.europa.eu/euodp/en/data/dataset/cordisH2020projects> (Accessed: 17 February 2021).
- Fang, Y., Cho, Y. K., Zhang, S. and Perez, E. (2016) 'Case Study of BIM and Cloud-Enabled Real-Time RFID Indoor Localization for Construction Management Applications', *Journal of Construction Engineering and Management*, 142(7), pp. 1–12. doi: 10.1061/(ASCE)CO.1943-7862.0001125.
- Field, A. (2009) *Discovering Statistics Using SPSS*, Sage Publication. doi: 10.1234/12345678.
- Giglio, N. M. (2010) *Architectural Graphic Standards for Residential Construction, 2nd Edition*, American Institute of Architects. Wiley & Sons.
- Goswami, C. and Saikia, K. K. (2012) 'FDI and its Relation with Exports in India, Status and Prospect in North East Region', *Procedia - Social and Behavioral Sciences*, 37, pp.

123–132. doi: 10.1016/j.sbspro.2012.03.280.

- Govada, S. S., Rodgers, T., Cheng, L. and Chung, H. (2020) *Smart environment for smart and sustainable Hong Kong, Advances in 21st Century Human Settlements*. Edited by T. M. V. Kumar. Singapore: Springer Nature Singapore Pte Ltd. doi: 10.1007/978-981-13-6822-6\_2.
- Gu, N. and London, K. (2010) 'Understanding and facilitating BIM adoption in the AEC industry', *Automation in Construction*. PO BOX 211, 1000 AE AMSTERDAM, NETHERLANDS: Elsevier B.V., 19(8), pp. 988–999. doi: 10.1016/j.autcon.2010.09.002.
- Gupta, A., Cemesova, A., Hopfe, C. J., Rezgui, Y. and Sweet, T. (2014) 'A conceptual framework to support solar PV simulation using an open-BIM data exchange standard', *Automation in Construction*. PO BOX 211, 1000 AE AMSTERDAM, NETHERLANDS: Elsevier B.V., 37, pp. 166–181. doi: 10.1016/j.autcon.2013.10.005.
- Hair, J. F., Anderson, R. E., Tatham, R. L. and Black, W. C. (2010) *Multivariate data analysis*. pper Saddle, New Jersey, USA: Prentice-Hall Inc.
- Hamma-adama, M., Salman, H. and Kouider, T. (2018) 'Diffusion of Innovations: The Status of Building Information Modelling Uptake in Nigeria', *Journal of Scientific Research and Reports*, 17(4), pp. 1–12. doi: 10.9734/jsrr/2017/38711.
- Hanna, A. S., Yeutter, M. and Aoun, D. G. (2014) 'State of Practice of Building Information Modeling in the Electrical Construction Industry', *Journal of Construction Engineering and Management - ASCE*. 1801 ALEXANDER BELL DR, RESTON, VA 20191-4400 USA: ASCE-AMER SOC CIVIL ENGINEERS, 140(12). doi: 10.1061/(ASCE)CO.1943-7862.0000893.
- HKGBC (2016) *BEAM Plus Existing Buildings Version 2.0 - Comprehensive Scheme*. 2.0. Hong Kong: Hong Kong Green Building Council. Available at: <http://bit.ly/2VYzq05>.
- HKGBC (2019) *BEAM Plus - New Buildings (Version 2.0)*. 2.0. Edited by BEAM Society Limited. Hong Kong: Hong Kong Green Building Council. Available at: <http://bit.ly/2mDw0yQ>.
- Hope, A. and Alwan, Z. (2012) 'Building the Future: Integrating Building Information Modelling and Environmental Assessment Methodologies', *Northumbria Research Link*. Available at: <https://core.ac.uk/download/pdf/8790178.pdf>.
- Hu, Y., Chan, A. P. C., Le, Y., Xu, Y. and Shan, M. (2016) 'Developing a Program Organization Performance Index for Delivering Construction Megaprojects in China: Fuzzy Synthetic Evaluation Analysis', *Journal of Management in Engineering*, 32(4), p.

05016007. doi: 10.1061/(ASCE)ME.1943-5479.0000432.

- IPCC (2007) *Climate Change 2007: Mitigation. Contribution of Working Group III to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change, Intergovernmental Panel on Climate Change*. Cambridge, UK: Cambridge University Press.
- Jalaei, F. and Jrade, A. (2014) 'Integrating Building Information Modeling (BIM) and Energy Analysis Tools with Green Building Certification System to Conceptually Design Sustainable Buildings', *Journal of Information Technology in Construction*, 19, pp. 494–519.
- Jalaei, F. and Jrade, A. (2015) 'Integrating building information modeling (BIM) and LEED system at the conceptual design stage of sustainable buildings', *Sustainable Cities and Society*. Elsevier B.V., 18, pp. 95–107. doi: 10.1016/j.scs.2015.06.007.
- Jeong, W. S., Chang, S., Son, J. W. and Yi, J. S. (2016) 'BIM-integrated construction operation simulation for just-in-time production management', *Sustainability*, 8(11), pp. 1–25. doi: 10.3390/su8111106.
- De Jong, M., Joss, S., Schraven, D., Zhan, C. and Weijnen, M. (2015) 'Sustainable-smart-resilient-low carbon-eco-knowledge cities; Making sense of a multitude of concepts promoting sustainable urbanization', *Journal of Cleaner Production*. Elsevier Ltd, 109, pp. 25–38. doi: 10.1016/j.jclepro.2015.02.004.
- Jung, W. and Lee, G. (2015) 'The Status of BIM Adoption on Six Continents', *International Journal of Civil, Structural, Construction and Architectural Engineering*, 9(5), pp. 406–410.
- Kassem, M., Brogden, T. and Dawood, N. (2012) 'BIM and 4D planning: a holistic study of the barriers and drivers to widespread adoption', *Journal of Construction Engineering and Project Management*, 2(4), pp. 1–10.
- Kivits, R. A. and Furneaux, C. (2013) 'BIM: Enabling sustainability and asset management through knowledge management', *The Scientific World Journal*, 2013. doi: 10.1155/2013/983721.
- Lam, K. C., Wang, D., Lee, P. T. K. and Tsang, Y. T. (2007) 'Modelling risk allocation decision in construction contracts', *International Journal of Project Management*, 25, pp. 485–493. doi: 10.1016/j.ijproman.2006.11.005.
- Lampreia, M., Santos, D. and Mota, M. (2019) 'Toward Sustainable and Smart Cities in Africa: A Review and Challenges', in Guedes, M. C. and Cantuaria, G. (eds) *Bioclimatic*

- Architecture in Warm Climates*. Switzerland: Springer Nature Switzerland AG 2019, pp. 299–309. doi: 10.1007/978-3-030-12036-8\_10.
- Liao, L., Teo Ai Lin, E. and Low, S. P. (2019) 'Assessing building information modeling implementation readiness in building projects in Singapore: A fuzzy synthetic evaluation approach', *Engineering, Construction and Architectural Management*, 27(3), pp. 700–724. doi: 10.1108/ECAM-01-2019-0028.
- Ljungberg, L. Y. (2007) 'Materials selection and design for development of sustainable products', *Materials and Design*, 28(2), pp. 466–479. doi: 10.1016/j.matdes.2005.09.006.
- Lu, Y., Wu, Z., Chang, R. and Li, Y. (2017) 'Building Information Modeling (BIM) for green buildings: A critical review and future directions', *Automation in Construction*. Elsevier, 83(January), pp. 134–148. doi: 10.1016/j.autcon.2017.08.024.
- Mahmoud, S., Zayed, T. and Fahmy, M. (2019) 'Development of sustainability assessment tool for existing buildings', *Sustainable Cities and Society*. Elsevier, 44(May 2017), pp. 99–119. doi: 10.1016/j.scs.2018.09.024.
- Maleki, M. Z. and Zain, M. F. M. (2011) 'Factors that influence distance to facilities in a sustainable efficient residential site design', *Sustainable Cities and Society*, 1, pp. 236–243.
- Martin, C., Evans, J., Karvonen, A., Paskaleva, K., Yang, D. *et al.* (2019) 'Smart-sustainability: A new urban fix?', *Sustainable Cities and Society*, 45(August 2018), pp. 640–648. doi: 10.1016/j.scs.2018.11.028.
- Martin, C. J., Evans, J. and Karvonen, A. (2018) 'Smart and sustainable? Five tensions in the visions and practices of the smart-sustainable city in Europe and North America', *Technological Forecasting and Social Change*. Elsevier, 133(July 2016), pp. 269–278. doi: 10.1016/j.techfore.2018.01.005.
- Mom, M., Tsai, M.-H. and Hsieh, S.-H. (2014) 'Developing critical success factors for the assessment of BIM technology adoption: Part II. Analysis and results', *Journal of the Chinese Institute of Engineers*. #1, 4TH FL, SEC 2, JEN-AI RD, TAIPEI 10019, TAIWAN: CHINESE INST ENGINEERS, 37(7), pp. 859–868. doi: 10.1080/02533839.2014.888798.
- Morlhon, R., Pellerin, R. and Bourgault, M. (2014) 'Building Information Modeling Implementation through Maturity Evaluation and Critical Success Factors Management', *Procedia Technology*. Elsevier B.V., 16, pp. 1126–1134. doi: 10.1016/j.protcy.2014.10.127.

- Motawa, I. and Carter, K. (2013) 'Sustainable BIM-based Evaluation of Buildings', *Procedia - Social and Behavioral Sciences*. Elsevier B.V., 74, pp. 419–428. doi: 10.1016/j.sbspro.2013.03.015.
- Nanajkar, A. and Gao, Z. (2014) 'BIM Implementation Practices at India's AEC Firms', in *International Conference on Construction and Real Estate Management*. Kunming, China.
- Olatunji, S. O., Olawumi, T. O. and Aje, I. O. (2017) 'Rethinking Partnering among Quantity-Surveying Firms in Nigeria', *Journal of Construction Engineering and Management*, 143(11), pp. 1–12. doi: 10.1061/(ASCE)CO.1943-7862.0001394.
- Olawumi, T. O. and Chan, D. W. M. (2018) 'A Scientometric Review of Global Research on Sustainability and Sustainable Development', *Journal of Cleaner Production*, 183(May), pp. 231–250. doi: 10.1016/j.jclepro.2018.02.162.
- Olawumi, T. O. and Chan, D. W. M. (2019a) 'An empirical survey of the perceived benefits of executing BIM and sustainability practices in the built environment', *Construction Innovation: Information, Process, Management*, 19(3), pp. 321–342. doi: 10.1108/CI-08-2018-0065.
- Olawumi, T. O. and Chan, D. W. M. (2019b) 'Development of a Benchmarking Model for BIM Implementation in Developing Countries', *Benchmarking: an International Journal*, 26(4), pp. 1210–1232. doi: 10.1108/BIJ-05-2018-0138.
- Olawumi, T. O. and Chan, D. W. M. (2020a) 'Application of Generalized Choquet Fuzzy Integral Method in the Sustainability Rating of Green Buildings based on the BSAM scheme', *Sustainable Cities and Society*, 61(October), p. Article Number 102147, 18 pages. doi: 10.1016/j.scs.2020.102147.
- Olawumi, T. O. and Chan, D. W. M. (2020b) 'Green-building information modelling (Green-BIM) assessment framework for evaluating sustainability performance of building projects : a case of Nigeria', *Architectural Engineering and Design Management*. Taylor & Francis, 0(0), pp. 1–20. doi: 10.1080/17452007.2020.1852910.
- Olawumi, T. O. and Chan, D. W. M. (2020c) 'Key drivers for smart and sustainable practices in the built environment', *Engineering, Construction and Architectural Management*, 27(6), pp. 1257–1281. doi: 10.1108/ECAM-06-2019-0305.
- Olawumi, T. O., Chan, D. W. M., Chan, A. P. C. and Wong, J. K. W. (2020) 'Development of a building sustainability assessment method (BSAM) for developing countries in sub-Saharan Africa', *Journal of Cleaner Production*. Elsevier Ltd, 263(August), p. Article Number 121514, 17 pages. doi: 10.1016/j.jclepro.2020.121514.



- Oloke, D. (2021) *Deployment of Building Information Modelling (BIM) for Energy Efficiency in the UK, Advances in Science, Technology and Innovation*. Springer International Publishing. doi: 10.1007/978-3-030-48465-1\_92.
- Osei-Kyei, R. and Chan, A. P. C. (2017) 'Developing a Project Success Index for Public–Private Partnership Projects in Developing Countries', *Journal of Infrastructure Systems*, 23(4), p. 04017028. doi: 10.1061/(ASCE)IS.1943-555X.0000388.
- Osei-Kyei, R. and Chan, A. P. C. (2018) 'Evaluating the project success index of public-private partnership projects in Hong Kong', *Construction Innovation*, 18(3), pp. 371–391. doi: 10.1108/CI-08-2017-0067.
- Ozorhon, B. and Karahan, U. (2016) 'Critical Success Factors of Building Information Modeling Implementation', *Journal of Management in Engineering*, 33(3), pp. 1–10. doi: 10.1061/(ASCE)ME.1943-5479.0000505.
- Park, C. S., Lee, D. Y., Kwon, O. S. and Wang, X. (2013) 'A framework for proactive construction defect management using BIM, augmented reality and ontology-based data collection template', *Automation in Construction*. Elsevier B.V., 33, pp. 61–71. doi: 10.1016/j.autcon.2012.09.010.
- Pedrycz, W., Ekel, P. and Parreiras, R. (2010) *Fuzzy Multicriteria Decision-Making: Models, Methods and Applications, Fuzzy Multicriteria Decision-Making: Models, Methods and Applications*. Chichester: John Wiley and Sons. doi: 10.1002/9780470974032.
- Redmond, A., Hore, A., Alshawi, M. and West, R. (2012) 'Exploring how information exchanges can be enhanced through Cloud BIM', *Automation in Construction*. Elsevier B.V., 24, pp. 175–183. doi: 10.1016/j.autcon.2012.02.003.
- Rivera, M. B., Eriksson, E. and Wangel, J. (2015) 'ICT practices in smart sustainable cities: In the intersection of technological solutions and practices of everyday life', in *29th International Conference on Informatics for Environmental Protection (EnviroInfo 2015). Third International Conference on ICT for Sustainability (ICT4S 2015)*. Atlantis Press, pp. 317–324.
- Rogers, J., Chong, H.-Y. and Preece, C. (2015) 'Adoption of Building Information Modelling technology (BIM) Perspectives from Malaysian engineering consulting services firms', *Engineering , Construction and Architectural Management*. HOWARD HOUSE, WAGON LANE, BINGLEY BD16 1WA, W YORKSHIRE, ENGLAND: EMERALD GROUP PUBLISHING LIMITED, 22(4), pp. 424–445. doi: 10.1108/ECAM-05-2014-0067.
- Russo, F., Rindone, C. and Panuccio, P. (2016) 'European plans for the smart city: from

- theories and rules to logistics test case', *European Planning Studies*, 24(9), pp. 1709–1726. doi: 10.1080/09654313.2016.1182120.
- Saini, N. and Singhanian, M. (2018) *Determinants of FDI in developed and developing countries: a quantitative analysis using GMM*, *Journal of Economic Studies*. doi: 10.1108/JES-07-2016-0138.
- Saka, A. B., Chan, D. W. M. and Olawumi, T. O. (2019) 'A Systematic Literature Review of Building Information Modelling in the Architecture, Engineering and Construction Industry - The Case of Nigeria', in *Proceedings of the Environmental Design and Management International Conference (EDMIC 2019) on Drivers and Dynamics of Change in the Built Environment*. 20-22 May 2019, Ile-Ife, Nigeria: EDMIC, pp. 728–738.
- Sato, T. (2005) *Factor analysis in personality psychology*.
- Saxon, R. G. (2013) 'Growth through BIM', *Construction Industry Council*. London.
- Shan, M., Chan, A. P. C., Le, Y., Xia, B. and Hu, Y. (2015) 'Measuring Corruption in Public Construction Projects in China', *Journal of Professional Issues in Engineering Education and Practice*, 141(4), p. Article Number 05015001. doi: 10.1061/(ASCE)EI.1943-5541.0000241.
- Shi, Q., Yan, Y., Zuo, J. and Yu, T. (2016) 'Objective conflicts in green buildings projects: A critical analysis', *Building and Environment*. Elsevier Ltd, 96, pp. 107–117. doi: 10.1016/j.buildenv.2015.11.016.
- Shmelev, S. E. and Shmeleva, I. A. (2019) 'Multidimensional sustainability benchmarking for smart megacities', *Cities*. Elsevier, 92(April 2018), pp. 134–163. doi: 10.1016/j.cities.2019.03.015.
- Shojaei, A., Wang, J. and Fenner, A. (2019) 'Exploring the feasibility of blockchain technology as an infrastructure for improving built asset sustainability', *Built Environment Project and Asset Management*, 10(2), pp. 184–199. doi: 10.1108/BEPAM-11-2018-0142.
- Shukla, M. and Mattar, L. (2019) 'Next generation smart sustainable auditing systems using Big Data Analytics: Understanding the interaction of critical barriers', *Computers and Industrial Engineering*. Elsevier, 128(May 2018), pp. 1015–1026. doi: 10.1016/j.cie.2018.04.055.
- Slimane, M. (2012) 'Role and relationship between leadership and sustainable development to release social, human, and cultural dimension', *Social and Behavioral Sciences*, 41,

pp. 92–99.

- Soyinka, O., Siu, K. W. M., Lawanson, T. and Adeniji, O. (2016) 'Assessing smart infrastructure for sustainable urban development in the Lagos metropolis', *Journal of Urban Management*. Elsevier B.V., 5(2), pp. 52–64. doi: 10.1016/j.jum.2017.01.001.
- Succar, B., Sher, W. and Williams, A. (2013) 'An integrated approach to BIM competency assessment, acquisition and application', *Automation in Construction*. PO BOX 211, 1000 AE AMSTERDAM, NETHERLANDS: Elsevier B.V., 35, pp. 174–189. doi: 10.1016/j.autcon.2013.05.016.
- Suermann, P. C. and Issa, R. R. A. (2009) 'Evaluating industry perceptions of building information modeling (BIM) impact on construction', *Electronic Journal of Information Technology in Construction*, 4(1), pp. 574–594.
- Tai, S., Zhang, Y. and Li, T. (2020) 'Factors affecting BIM application in China: a social network model', *Journal of Engineering, Design and Technology*. doi: 10.1108/JEDT-12-2019-0330.
- Tam, V. W., Le, K. N., Tran, C. N. and Illankoon, I. C. S. (2019) 'A review on international ecological legislation on energy consumption: greenhouse gas emission management', *International Journal of Construction Management*, pp. 1–12. doi: 10.1080/15623599.2019.1576259.
- Terwase, I. T., Abdul-Talib, A. N. and Zengeni, K. T. (2014) 'Nigeria, Africa's largest economy: International business perspective', *International Journal of Management Sciences*, 3(7), pp. 534–543.
- Toor, S. and Ofori, G. (2008) 'Leadership for future construction industry: Agenda for authentic leadership', *International Journal of Project Management*, 26, pp. 620–630. doi: 10.1016/j.ijproman.2007.09.010.
- Tsai, M.-H., Mom, M. and Hsieh, S.-H. (2014) 'Developing critical success factors for the assessment of BIM technology adoption: part I. Methodology and survey', *Journal of the Chinese Institute of Engineers*. #1, 4TH FL, SEC 2, JEN-AI RD, TAIPEI 10019, TAIWAN: CHINESE INST ENGINEERS, 37(7), pp. 845–858. doi: 10.1080/02533839.2014.888811.
- UNEP (2011) *Towards a green economy: Pathways to sustainable development and poverty eradication*. Nairobi, Kenya: United Nations Environment Programme.
- Ürge-Vorsatz, D., Harvey, L. D. D., Mirasgedis, S. and Levine, M. D. (2007) 'Mitigating CO2 emissions from energy use in the world's buildings', *Building Research and Information*,

35(4), pp. 379–398. doi: 10.1080/09613210701325883.

USGBC (2018) *LEED v4 for Interior Design and Construction*. 4th edn. Washington D.C.: U.S. Green Building Council.

Won, J. and Lee, G. (2010) 'Identifying the consideration factors for successful BIM projects', in *Proceedings of the International Conference on Computing in Civil and Building Engineering*. Nottingham: The University of Nottingham, pp. 143–148. Available at: <https://bit.ly/2Q9I07P>.

Wong, A. K. D., Wong, F. K. W. and Nadeem, A. (2009) 'Attributes of Building Information Modelling and its Development in Hong Kong', *HKIE Transactions*, 16(2), pp. 1–8.

Wong, J. K. W. and Zhou, J. (2015) 'Enhancing environmental sustainability over building life cycles through green BIM: A review', *Automation in Construction*. PO BOX 211, 1000 AE AMSTERDAM, NETHERLANDS: Elsevier B.V., 57, pp. 156–165. doi: 10.1016/j.autcon.2015.06.003.

Wong, K. and Fan, Q. (2013) 'Building information modelling (BIM) for sustainable building design', *Facilities*, 31(3), pp. 138–157. doi: 10.1108/02632771311299412.

World Bank (2020) *World Bank Country and Lending Groups*, *World Bank*. Available at: <https://datahelpdesk.worldbank.org/knowledgebase/articles/906519>.

Xu, Y., Yeung, J. F. Y., Chan, A. P. C., Chan, D. W. M., Wang, S. Q. *et al.* (2010) 'Developing a risk assessment model for PPP projects in China-A fuzzy synthetic evaluation approach', *Automation in Construction*. Elsevier B.V., 19(7), pp. 929–943. doi: 10.1016/j.autcon.2010.06.006.

Yeomans, S. G., Bouchlaghem, N. M. and El-Hamalawi, A. (2006) 'An evaluation of current collaborative prototyping practices within the AEC industry', *Automation in Construction*, 15(2), pp. 139–149.

Yeung, J. F. Y., Chan, A. P. C. and Chan, D. W. M. (2009) 'Developing a Performance Index for Relationship-Based Construction Projects in Australia: Delphi Study', *Journal of Management in Engineering*, 25(2), pp. 59–68. doi: 10.1061/(ASCE)0742-597X(2009)25:2(59).

Yuan, H., Yang, Y. and Xue, X. (2019) 'Promoting Owners' BIM Adoption Behaviors to Achieve Sustainable Project Management', *Sustainability*, 11, pp. 1–18. doi: 10.3390/su11143905.

Zhao, D. X., He, B. J., Johnson, C. and Mou, B. (2015) 'Social problems of green buildings: From the humanistic needs to social acceptance', *Renewable and Sustainable Energy*

*Reviews*. Elsevier, 51, pp. 1594–1609. doi: 10.1016/j.rser.2015.07.072.

Zhao, X., Hwang, B. G. and Gao, Y. (2016) 'A fuzzy synthetic evaluation approach for risk assessment: A case of Singapore's green projects', *Journal of Cleaner Production*. Elsevier Ltd, 115(January 2005), pp. 203–213. doi: 10.1016/j.jclepro.2015.11.042.